

# KV660 Aramid Oil Resistant



## Aramid knit PVC coating

### DESCRIPTION

- Fully coated, extra coating over entire hand
- Scalloped edge
- Rough finish over entire surface
- Special hydrocarbon treatment
- Antibacterial and anti-odour treatment
- Kevlar® fibre
- Anatomical shape
- Seamless knit

### BENEFITS

- A flexible easy-maintenance glove providing effective protection against cuts and with very good durability
- Seals and protects the hand against chemicals while remaining flexible
- Impermeable for working in damp or greasy environments, enabling you to grip objects securely
- Surface provides tactile feel and better grip
- Greater hygiene
- Designed for easy movement and continuous wear
- No irritation by seams in contact with the skin
- Extended protection on the forearm

Kevlar® is a registered trademark of E.I. du Pont de Nemours and Company



### RECOMMENDED FOR THESE RISKS:

Cold  
Cuts  
Chemicals  
Oils  
Hydrocarbons

### RECOMMENDED FOR THESE LINES OF WORK:

Chemical industry / Acid components  
Chemical industry / Solvents  
Petrochemistry

### AVAILABLE SIZES

8/M • 9/L • 10/XL • 11/XXL

### LENGTH

Dependent on size, in mm (flat)

300-320

### PACKAGING

Pairs per pack/box

10/120

### COLOUR OF SUPPORT/COATING

Blue

### THICKNESS

in mm

1,30

### RECOMMENDATIONS FOR USE

- Do not use with chemicals other than those tested without prior trials
- The stated impermeability performance level (EN374-3) does not reflect the actual protection level at the place of work – other factors may influence the performance.
- Highly traction resistant gloves, do not use if there is risk of being caught up in moving machines
- Store away from light and humidity
- Rinse the gloves in running water before removing, using a neutral detergent if necessary

from  
**Globus**®

Globus (Sheltand) Ltd  
PO Box 564  
MANCHESTER  
M6 0EX, UK

Tel: 0161 877 4747 Fax: 0161 877 4746  
www.globus.co.uk

EC compliance certificate delivered by the notified body 0120 SGS Yarsley International Certification Services Ltd  
SGS House, 217-221 London Road Camberley, Surrey, GU15 3EY – United Kingdom

The descriptions, characteristics, applications and photos are given for information purposes and do not constitute a contractual commitment. The manufacturer reserves the right to make any modifications it deems necessary.

Cat. III	EN388 - 2003	ABRASION	CUTTING	EN 374-2 - 2003	EN 374-3 - 2003	J - N-HEPTANE	K - CAUSTIC SODA 40%
CE		0 1 2 3 4	0 1 2 3 4 5			0 1 2 3 4 5 6	0 1 2 3 4 5 6
0120	4342	TEARING	PUNCTURE			L - SULPHURIC ACID 96%	
		0 1 2 3 4	0 1 2 3 4		J K L	0 1 2 3 4 5 6	

[ Updated 17/03/2014 ]

**SHOWA**

The Ultimate in Comfort and Dexterity